

FEB 1952 51-4AA

REF ID: A66004  
COPY

DO NOT CIRCULATE

CENTRAL INTELLIGENCE AGENCY

CLASSIFICATION SECRET/

25X1

## INFORMATION REPORT

REPORT NO.

25X1

CD NO.

COUNTRY Hungary

DATE DISTR. 23 October 1952

SUBJECT The Tisza Power Project

NO. OF PAGES 2

DATE OF INFO.

NO. OF ENCLS. 2 sketches  
(LISTED BELOW)

PLACE ACQUIRED

SUPPLEMENT TO  
REPORT NO.

25X1

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES, WITHIN THE MEANING OF TITLE 18, SECTIONS 793 AND 794, OF THE U.S. CODE, AS AMENDED. ITS TRANSMISSION OR REVELATION OF ITS CONTENTS TO OR RECEIPT BY AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW. THE REPRODUCTION OF THIS FORM IS PROHIBITED.

THIS IS UNEVALUATED INFORMATION

1. Construction of this plant, which has a generating capacity of 20,000 kw., was begun in 1945 during the last months of the war. The plant supplies power to the Diósgyőr Steel Works.
2. Water is obtained from the Hernád River. A lock, located between Belsőbócs and Külsőbócs, distributes the water over an area of 2,000 sq. m.. The reservoir which is located behind this area is separated from the canal by three locks.
3. The conducting canal (No. 1 on sketch II) is 2,600 m. long; its sides are covered with stone. The bottom has a width of 6 m. and the surface a width of 14 m.. The canal conducts the water to pipes (No. 2). (See the profile: No. 2a.) Just before reaching the pipes the canal has a double width.
4. The canal is separated from the pipes by a lock (No. 3). When the lock is open, the water falls 14 m. through the pipes on the turbines (No. 4). Each of the two pipes can be operated independently. The pipes are made of concrete and are as smooth as glass.
5. The turbine chambers are equipped with two turbines made by Ganz. The turbines have vertical axes. The power is conducted from the turbine chambers to the two Ganz generators in the machine house (No. 5) which can also function separately. The transformer house (No. 6) is located at + 10 m., while the turbine chambers are at - 10 m.. The current is transmitted from the main control room to the cables which conduct the power to the Diósgyőr Steel Works.
6. Drainage (No. 8) is maintained by having the water flow through the turbines and through an opening into the canal (through a fall of - 10 m. and at a slope of 6 percent) and further on into the Tisza River.

CLASSIFICATION SECRET/

25X1

STATE	X	NAVY	X	NSRB		DISTRIBUTION									
ARMY	X	AIR	X	FBI		ORR	EV	X							

SECRET/

- 2 -

7. All equipment was made and set up by Ganz.

Enclosures: Sketch I. Area of the Tiszaaluc Power Project  
Sketch II. The Tiszaaluc Power Plant.

SECRET/

25X1


25X1

SECRET

25X1


Sketch I

Area of Tisza River Power Project



Sketch II

The Tisza River Power Plant



SECRET

25X1